

SXC-FP530-F


AMD Ryzen™ Embedded R2000 Series Processor based Mini PC
supports four displays with 4HDMI2.0, 2LAN, 2COM, 7USB



Features

- CPU: AMD Ryzen™ Embedded R2000 Series Processor
- Memory: Dual Channel SO-DIMM DDR4 up to 64GB
- GPU: AMD Radeon™ Graphics, support four displays up to 4K@60Hz
Support HDMI Hot-Plug Lock, RTC/W
- Ethernet: 2xRealtek RTL8111H(10/100/1000/Mbps)
- Storage: M.2 Key M for NVMe/SATA, M.2 Key B for SATA SSD/4G
- I/O Ports: 2xLAN, 2xCOM, 2xUSB3.2, 4xUSB2.0, 4xHDMI2.0, USB-C
- Expansion: M.2 Key E for Wi-Fi and Bluetooth, Nano SIM
- Power: 12V/19V DC-IN

AMD
together we advance_



Introduction

Maxtang SXC-FP530-F is a compact embedded mini PC powered by the AMD Ryzen™ Embedded R2000 Series processor with integrated AMD Radeon™ Graphics, delivering high-performance computing and advanced multi-display capability. It supports up to four HDMI 2.0 outputs, making it suitable for digital signage, control centers, and industrial applications requiring synchronized, high-quality visuals.

Designed for demanding environments, the SXC-FP530-F provides versatile connectivity with dual Gigabit LAN, two COM ports (RS232/RS485 optional), seven USB ports, and M.2 expansion. Its rugged design, active cooling, and wide-range 12V/19V DC-IN ensure stable operation from -20°C to 60°C. With optional TPM, Real-Time Clock scheduling, and support for both Windows and Linux, the system offers enhanced security, manageability, and flexibility for industrial automation, AI edge computing, and multi-display deployments.




H/W Monitor



Watchdog




I/O Interfaces



Technical Specifications

Processor	AMD Ryzen™ Embedded	R2314	R2514
	Total Cores/Threads	4C/4T	4C/8T
	Base Frequency	2.10GHz	2.10GHz
	Max Frequency	3.50GHz	3.70GHz
	Total L3 Cache	4MB	4MB
	TDP	35W	35W
	GPU	AMD Radeon™ Graphics	
	BIOS	AMI UEFI BIOS	
Memory	Type	Dual Channel SO-DIMM DDR4	
	Max. Capacity	64GB	
Display	Graphics	Integrated Graphics depends on the CPU model, see GPUs.	
	Display via	4x HDMI2.0	
	Max Resolution	Up to 4K @ 60Hz	
		HDMI Hot-Plug Lock	
Ethernet	Controller	2xRealtek 8111H	
	Max. Speed	10/100/1000Mbps	
	Interface	2x RJ45	
	Wake on LAN	Yes	
Audio	Audio Codec	Realtek ALC897 High Definition Audio Codec	
	Interface	1x Line-out, 1xMic-in	
Storage	M.2_N/S	1x M.2 Key_M Slot for 2280 NVMe/SATA SSD	
	M.2_S/W	1x M.2 Key_B Slot for 2242/2280 SATA SSD or 3042 4G Module	
Expansion	M.2_E	1x M.2 Key_E Slot for 2230 Wi-Fi and Bluetooth Module	
	Nano SIM	1x Nano SIM Slot	
Other I/O	COM	2x COM(RS232 by default, RS485 optional through hardware changes)	
	USB2.0	4	
	USB3.2	2	
	USB-C	1xUSB-C(Supports USB3.2 only)	
	Wired Control	1	
	TPM	Onboard, optional	
Real Time Clock	RTC	Support RTC set up, independently for each day of the week.	
Dimension	Size	190mm x 150mm x 35mm	
Weight	N.W.	1.06KG	
Power	Standard Port	12V/19V DC-IN	
Temperature	Operating Temp.	- 20°C to 60°C	
	Storage Temp.	- 40°C to 80°C	
Cooling Method		Active	
Operating System		Windows 10/11 64bit, Linux 64bit	

Dimension (in mm)



Copyright © 2025 Maxtang Technology Co., Ltd. All rights reserved. All data is for information purposes only and not guaranteed for legal purposes. Information has been carefully checked and is believed to be accurate however, no responsibility is assumed for inaccuracies. Maxtang and the Maxtang logo and all other trademarks or registered trademarks are the property of their respective owners and are recognized. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress, and HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.