

# IXH-ALN35

Intel® Alder Lake-N Series based Embedded Fanless Industrial PC



## Features

- CPU: Intel® Alder Lake-N Series Processor
- Memory: Single Channel SO-DIMM DDR4 up to 16 GB
- Display: Intel Integrated Graphics, display via HDMI®+DP
- Ethernet: 10/100/1000Mbps
- Storage: SATA3.0, mSATA
- Expansion: M.2 for WiFi
- Power: 9V-35V DC input, Phoenix input optional



## Introduction

The Maxtang IXH-ALN35 is a compact, embedded industrial PC powered by the Intel® Alder Lake-N series processor. It supports up to 8Cores 8Threads, 6M Cache, and 3.80GHz for Max Turbo frequency. Equipped 1xSO-DIMM DDR4 max to 16GB memory and a TDP rate of 12W-15W for energy saving. A rich I/O interface includes HDMI, DP, two RJ45 gigabit network controllers, six serial ports (default 4\*RS232+2\*RS485), and eight USB ports that suit most market requirements.

The IXH-ALN35 includes a comprehensive I/O interface for easy integration and a ruggedized design for harsh environments. It has a long-lasting life cycle based on its stability and reliability. It is made with an aluminum enclosure that contains a fanless structure intended to protect internal components from dust and debris in a harsh industrial environment.



H/W Monitor



Watchdog




GPIO



Brightness



## I/O Interfaces




## Technical Specifications

Processor	CPU	Core i3-N305	N97
	Total Cores/Threads	8C/8T	4C
	Max Turbo Frequency	3.80GHz	3.60GHz
	Intel® Smart Cache	6MB	6MB
	TDP	15W	12W
	BIOS	AMI UEFI BIOS	
Memory	Type	Single Channel SO-DIMM DDR4	
	Max Capacity	16GB	
Display	GPU	Integrated Intel® UHD Graphics	
	Display via	1xHDMI2.0 + 1xDP	
Ethernet	Speed	10/100/1000Mbps	
	Controller	2x Intel i210	
	Interface	2x RJ45	
	Wake on LAN	Yes	
Audio	Audio Codec	Realtek HD	
	Interface	1xCTIA 2-in-1 Audio Jack	
Hardware		System temperature, Onboard voltage, Watchdog, Auto power on	
Storage	mSATA	1x mSATA for SSD/4G Module	
	SATA	1x SATA3.0 for 2.5-inch HDD	
Expansion	M.2	1x M.2_E for Wi-Fi, support Intel® Integrated Connectivity (CNVi)	
I/O Interface	COM	6xCOM: default 4*RS232+2*RS485(COM5,COM6), optional 6*RS232.	
	USB2.0	4x USB2.0	
	USB3.0	4x USB3.2	
	GPIO	8-bit	
	Wired Control	1	
Dimension	Size	205mm x 125mm x 70.5mm	
Power	Standard Input	9V-35V DC-IN	
	Optional	Phoenix 3-pin optional	
	Peripheral Input	For Fan and SATA	
	LED Indicator	Power indicator	
Temperature	Operating Temp.	-20°C to 60°C	
	Storage Temp.	-40°C to 80°C	
Cooling		Passive	
Operating System		Win10/11 64bit, Linux 64 bit	

\*All specifications and photos are subject to change without notice.

## Dimensions



IXH-ALN35

Copyright © 2025 Maxtang Technology Co., Ltd. All rights reserved. All data is for information purposes only and not guaranteed for legal purposes. Information has been carefully checked and is believed to be accurate however, no responsibility is assumed for inaccuracies. Maxtang and the Maxtang logo and all other trademarks or registered trademarks are the property of their respective owners and are recognized. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress, and HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.