

# VBYT-30

Intel Bay Trail Processors based Fanless  
Embedded Mini PC



## Features

- CPU: Intel Bay Trail Processors
- Memory: 2x SO-DIMM DDR3L up to 8GB
- Display via: Intel HD Graphics display via HDMI, VGA
- I/O Ports: 3xLAN, 2x COM, 1xUSB3.2, 5xUSB2.0.
- Ethernet: 10/100/1000Mbps
- Storage: SATA, mSATA
- Power: 12/19 V DC-in




## Introduction

The VBYT-30 is a small form factor embedded fanless PC based on the Intel® Bay Trail platform. It supports Intel® Celeron™ J1900, J1800, N2940, and ATOM-E E3845 for better performance with cost advantages. The PC carries 2 SO-DIMM DDR3L memories up to 8GB to add higher bandwidth, lower latencies for processes. It features Intel Integrated graphic display via 1×HDMI and 1×VGA, supports dual independent playback.

A rich i/o interface includes 3xLAN, 2xCOM, 1xUSB3.2, and 5xUSB2.0 meets most market's requirements. 1x mini-PCIe for Wi-Fi, 1x SIM card slot for expansion, and a desktop ready for easy installation. Its fanless construction not only overcomes noise challenges but also can be a great fit for various applications. The VBYT-30 provides an excellent customer experience, a long-lasting life expectancy for future development.



## I/O Interfaces




## Technical Specifications

Processor	CPU	J1800	J1900	N2940	E3845
	Core Frequency	2.41 GHz	2.0 GHz	1.83 GHz	1.91 GHz
	Max Turbo Frequency	2.58 GHz	2.42 GHz	2.25 GHz	/
	Cache	1MB	2MB	2MB	2MB
Memory	Type	2x SO-DIMM DDR3L			
	Max. Capacity	8 GB			
Display	GPU	Intel HD Graphics based on CPU			
	Display via	HDMI+ VGA			
Ethernet	Speed	10/100/1000 Mbps			
	Controller	Realtek RTL8111H			
	Interface	RJ45			
	Wake on LAN	Yes			
Audio	Audio Codec	Realtek HD			
	Interface	1xLine-out, 1xMic-in			
Storage	SATA3.0	1			
	mSATA	1			
Expansion	mini-PCIe	1x mini-PCIe for WiFi			
	SIM Card Slot	1x Internal Micro SIM Card Slot			
I/O	LAN	3xLAN or 1xLAN			
	COM	2x RS232(RS485 Optional)			
	USB2.0	5			
	USB3.2	1			
	HDMI	1			
	VGA	1			
Dimension	Size	190 mm x 150mm x 29 mm			
Weight(kg)	N.W.	860g			
Power	Standard Port	12/19 V DC-in			
Temperature	Operating Temp.	- 20°C to 60°C			
	Storage Temp.	- 20°C to 80°C			
Cooling Method		Passive			
Operating System		Windows 7/8/10, Linux			

\* All specifications and photos are subject to change without notice.

### Dimension (in mm)



Copyright © 2018 Maxtang Technology Co., Ltd. All rights reserved. All data is for information purposes only and not guaranteed for legal purposes. Information has been carefully checked and is believed to be accurate however, no responsibility is assumed for inaccuracies. Maxtang and the Maxtang logo and all other trademarks or registered trademarks are the property of their respective owners and are recognized.