

VHBYT-30

Intel Bay Trail Processors based Fanless
Embedded Mini PC



Features

- CPU: Intel Bay Trail Processors
- Memory: 2x SO-DIMM DDR3L up to 8GB
- Display via: Intel HD Graphics display via HDMI, VGA
- I/O Ports: 3xLAN, 2x COM, 1xUSB3.2, 5xUSB2.0.
- Ethernet: 10/100/1000Mbps
- Storage: SATA3.0, mSATA
- Power: 12/19V DC-in




Introduction

Maxtang's VHBYT-30 fanless embedded mini-PC incorporated the Intel Bay Trail processors, offers you greater computing power with cost advantages. Dual-channel SO-DIMM DDR3L for its memory, dual display via HDMI and VGA. A rich i/o interface includes 3xLAN, 2xCOM, 1xUSB3.2, and 5xUSB2.0 meets most market's requirement. It provides an excellent customer experience, a long-lasting life expectancy for future development.

Based on a small form factor, as its name states, it is great for space-saving. It has one mini-PCIe for WiFi, one SIM card slot for expansion, and desktop ready for easy installation. Fanless construction not only overcomes noise challenges but also can be a great fit for various applications.



I/O Interfaces




Technical Specifications

| | | |
|------------------|---------------------|---------------------------------|
| Processor | CPU | J1900 |
| | Core Frequency | 2.0 GHz |
| | Max Turbo Frequency | 2.42 GHz |
| | Cache | 2MB |
| | TDP | 10W |
| Memory | Type | 2x SO-DIMM DDR3L |
| | Max. Capacity | 8 GB |
| Display | GPU | Intel HD Graphics based on CPU |
| | Display via | HDMI+ VGA |
| Ethernet | Speed | 10/100/1000 Mbps |
| | Controller | Realtek RTL8111H |
| | Interface | RJ45 |
| | Wake on LAN | Yes |
| Audio | Audio Codec | Realtek HD |
| | Interface | Line-out, mic-in |
| Storage | SATA3.0 | 1 |
| | mSATA | 1 |
| Expansion | mini-PCIe | 1x mini-PCIe for WiFi |
| | SIM Card Slot | 1x Micro SIM Card Slot Internal |
| I/O | LAN | 3 |
| | COM | 2x RS232 |
| | USB2.0 | 5 |
| | USB3.2 | 1 |
| | HDMI | 1 |
| | VGA | 1 |
| Dimension | Size | 191 mm x 151mm x 34 mm |
| Weight(kg) | N.W. | 1 kg |
| Power | Standard Port | 12/19V DC-in |
| Temperature | Operating Temp. | - 20°C to 60°C |
| | Storage Temp. | - 20°C to 80°C |
| Cooling Method | | Passive |
| Operating System | | Windows 7/8/10, Linux |

* All specifications and photos are subject to change without notice.

Dimension (in mm)



Copyright © 2018 Maxtang Technology Co. Ltd. All rights reserved. All data is for information purposes only and not guaranteed for legal purposes. Information has been carefully checked and is believed to be accurate however, no responsibility is assumed for inaccuracies. Maxtang and the Maxtang logo and all other trademarks or registered trademarks are the property of their respective owners and are recognized.