


AL-10

PRODUCT DATASHEET
HW Rev.: V2.0

Intel® Alder Lake/Raptor Lake-U/P Series Processor based
Mini ITX Motherboard with 6COM, 4HDMI



Features

- CPU: Intel® Alder Lake/Raptor Lake-U/P series processor
- Memory: Dual channel SO-DIMM DDR4 up to 64GB
- GPU: Intel Iris® Xe Graphics eligible/UHD Graphics, display via 4xHDMI+LVDS
- Ethernet: Intel® i226(2.5GbE) + Intel® i219(1.0GbE)
- Storage: M.2 Key M for NVMe SSD, M.2 Slot for SATA SSD/4G, SATA3.0
- Expansion: M.2 Key E for WiFi & BT, PCIe x4 Slot
- Power: 19V/12V DC-in



Introduction

The Maxtang AL10 is a compact and versatile Mini-ITX industrial motherboard built on the latest 12th Gen Intel® Alder Lake processors (P and U series). Offering a wide range of CPU options from Core™ i7, i5, to i3, it delivers up to 12 cores and 16 threads with efficient performance per watt. Supporting dual-channel DDR4 memory up to 64GB and Intel Iris® Xe/UHD Graphics, the board is capable of driving up to four independent 4K displays via HDMI and LVDS/eDP interfaces, making it ideal for digital signage, retail solutions, kiosks, industrial automation, and multi-screen environments.

To meet diverse application needs, the AL10V2.0 integrates dual Intel Ethernet controllers (2.5GbE + 1GbE), M.2 NVMe/SATA storage expansion, M.2 Key B for 4G modules with Nano SIM support, M.2 Key E for WiFi/BT, and a PCIe x4 Gen 4 slot for additional add-ons. Rich I/O includes 6 COM ports, multiple USB3.2/USB2.0, GPIO, and Realtek ALC897 audio, alongside essential industrial features such as TPM 2.0 security, watchdog timer, hardware monitoring, and auto power-on. With its 19V DC input, wide -20°C to 60°C operating temperature range, and reliable Mini-ITX 170mm x 170mm design, the AL10V2.0 delivers a flexible, secure, and high-performance platform tailored for embedded and industrial computing applications.



H/W Monitor



Watchdog




GPIO



Brightness




I/O Interfaces



Technical Specifications

Processor	Alder Lake P Series	i7-1260P	i5-1240P	i3-1220P
	Total Cores/Threads	12C/16T	12C/16T	10C/12T
	P-core Max Turbo Frequency	4.70 GHz	4.40 GHz	4.40 GHz
	E-core Max Turbo Frequency	3.40 GHz	3.30 GHz	3.30 GHz
	Cache	8 MB	12 MB	12 MB
	Processor base Power	28 W	28 W	28 W
Processor	Alder Lake U Series	i7-1255U	i5-1235U	i3-1215U
	Total Cores/Threads	10C/12T	10C/12T	6C/8T
	P-core Max Turbo Frequency	4.70 GHz	4.40 GHz	4.40 GHz
	E-core Max Turbo Frequency	3.50 GHz	3.30 GHz	3.30 GHz
	Cache	12 MB	12 MB	10 MB
	Processor base Power	15 W	15 W	15 W
Memory	BIOS	AMI UEFI BIOS		
	Type	Dual Channel SO-DIMM DDR4		
	Max.Capacity	64GB		
Display	GPU	Integrated Intel Iris® Xe Graphics eligible/UHD Graphics		
	Interface	4 x HDMI2.0+1x LVDS/eDP		
		support four 4K independent displays. Max. four screens for mutiple displays.		
Ethernet	Controller	1 x Intel i226, Data Rate Per Port: 2.5GbE		
		1 x Intel i219, Data Rate Per Port: 1.0GbE		
	Interface	2 x RJ45		
Audio	Wake on LAN	Yes		
	Audio Codec	Realtek HD ALC897		
	Interface	1 x Line-out, 1xMic-in, supports audio header and amplifier header		
Hardware Monitoring		CPU system temperature, onboard voltage, watchdog, auto power on		
Storage	M.2_N	1 x M.2 Key M for 2280 NVMe SSD		
	M.2_S	1xM.2 Key B for 2242 SATA SSD or 4G Module		
	SATA	1 x SATA3.0		
Expansion	M.2_E	1 x M.2 Key E for 2230 WiFi and Bluetooth, support CNVi		
	PCIe x4	1*PCIe x4 Gen 4 Slot		
	SIM	1x Nano SIM Slot		
Other I/O	COM	6 x COM: 6*RS232 by default, or 5*RS232+1*RS485(COM1) optional		
	USB3.2	4 x USB3.2(ports)		
	USB2.0	4 x USB2.0(headers)		
	GPIO	8-bit		
	TPM2.0	Onboard, optional		
	Size	170mm x 170mm		
Power	Form Factor	Mini-ITX		
	Standard Port	19V/12V DC-in		
	Peripheral Input	For Fan and SATA		
Operating System	Operating Temp.	-20°C ~60°C		
	Storage Temp.	-40°C ~80°C		
		Win10/11 64 bit, Linux 64 bit		

Block Diagram



Copyright © 2025 Maxtang Technology Co. Ltd. All rights reserved. All data is for information purposes only and not guaranteed for legal purposes. Information has been carefully checked and is believed to be accurate however, no responsibility is assumed for inaccuracies. Maxtang and the Maxtang logo and all other trademarks or registered trademarks are the property of their respective owners and are recognized. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress, and HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Order Information

Model Name	Description
DT1250P-A	DT MINI-ITX Intel Core i5-1250P AL10V20 2LAN 6*RS232 4HDMI+LVDS
DT1235U-A	DT MINI-ITX Intel Core i5-1235U AL10V20 2LAN 6*RS232 4HDMI+LVDS
DT1255U-A	DT MINI-ITX Intel Core i7-1255U AL10V20 2LAN 6*RS232 4HDMI+LVDS

***For customized options, please consult regional sales. And please confirm the model name and description before purchasing.

***The model name and description might vary due to inventory changes.