


FP-710

AMD® Ryzen™ AI Pro 8000 Series Processor


“Zen 4” Architecture based Mini ITX with 4 DisplayPorts



Features

- CPU: AMD Ryzen™ PRO 8845HS Processor
- Memory: Dual Channel SO-DIMM DDR5 up to 96GB
- Display: AMD Radeon™ Graphics, Up to 4 independent 4K displays
- Ethernet: Realtek® RTL8111H(1.0GbE)+RTL8125(2.5GbE)
- Storage: 2xM.2 Key M_2280 Slots for NVMe SSD
- Expansion: PCIe 4X, M.2 for Wi-Fi
- Power: DC-IN Jack

AMD
together we advance_



Introduction

The Maxtang FP-710 Mini-ITX motherboard is powered by AMD Ryzen™ 7 PRO 8845HS processor, offering up to 8 cores and 16 threads based on the advanced “Zen 4” architecture. With integrated AMD Ryzen™ AI technology and a dedicated Neural Processing Unit (NPU), it delivers powerful AI processing for enhanced productivity, creativity, and next-gen PC experiences. Designed for high performance and energy efficiency, the FP-710 is an ideal solution for a wide range of embedded applications.

This compact Mini ITX motherboard supports up to 96GB DDR5 memory via 2x SO-DIMM slots, 4x DisplayPort 1.4 outputs for four independent 4K displays, dual M.2 2280 slots for NVMe storage, and an M.2 2230 slot for Wi-Fi. It also offers optional TPM support for improved security with a rich set of I/O ports, including 6x COM, 8x USB, GPIO, Line-out, and Mic-in. Whether for electronic gaming, digital signage, or medical imaging, the FP-710 delivers the performance and connectivity modern industries demand.



H/W Monitor



Watchdog




GPIO



Brightness

I/O Interfaces




Technical Specifications

Processor	CPU	Ryzen™ 7 PRO 8845HS
	Cores/Threads	8C/16T
	Max. Boost Clock	Up to 5.1 GHz
	Base Clock	3.8 GHz
	L2/L3 Cache	8MB/16MB
AI Capabilities	AMD Ryzen™ AI	Available
	BIOS	AMI SPI BIOS
Memory	Type	Dual Channel SO-DIMM DDR5
	Max. Capacity	96GB
Display	GPU	AMD Radeon™ 780M Graphics
		Four 4K Displays. Resolution up to 4096x2160 for single displays.
Ethernet	Interface	4 xDP1.4
	Controller	Realtek® RTL8111H. Max.Speed:10/100/1000Mbps
		Realtek® RTL8125. Max.Speed:10/100/1000/2500Mbps
Audio	Interface	2xRJ45
	Audio Codec	Realtek® ALC897 High-definition Audio Codec
	Interface	1xLine-out, 1xMic-in, support audio header and amplifier header
Hardware Monitoring		CPU system temperature, onboard voltage, watchdog
Storage	M.2_N	2xM.2 Key M_2280 Slots for NVMe SSD
Expansion	M.2_E	1xM.2 Key E_2230 Slot for Wi-Fi and Bluetooth
	PCIe 4X	1
Other I/O	COM	6×RS232 (COM2 can be set as RS485 through hardware changes)
	USB3.2	2
	USB2.0	6 (2*Port + 4*header)
	GPIO	8-bit
	Buzz_M	Yes
	TPM2.0	Onboard, Optional
Dimension	Form Factor	Mini ITX
	Size	170 mm x 170 mm
Power	Standard Port	DC-IN Jack (Option 1: 19V / Option 2: 12V)
Temperature	Operating Temp.	-20°C ~60°C
	Storage Temp.	-40°C ~80°C
Operating System		Windows 10/11 64bit, Linux 64bit

*Image is for reference only. *All specifications and photos are subject to change without notice.

Block Diagram



Copyright ©2025 Maxtang Technology Co. Ltd. All rights reserved. All data is for information purposes only and not guaranteed for legal purposes. Information has been carefully checked and is believed to be accurate however, no responsibility is assumed for inaccuracies. Maxtang and the Maxtang logo and all other trademarks or registered trademarks are the property of their respective owners and are recognized.

Order Information

SKUs	Description
DT8845HS-A-12V	DT AMD 8845HS PRO FP710 DDR5 2LAN 6COM 4DP PCIE4X 2*NVME 12V NO POWER ADAPTER
DT8845HS-A-19V	DT AMD 8845HS PRO FP710 DDR5 2LAN 6COM 4DP PCIE4X 2*NVME 19V POWER ADAPTER OPTIONAL

*For customization, please contact your regional sales representative. Confirm model details before purchase, as they may vary.